## TOWN OF NEW WINDSOR



## WATER DEPARTMENT

555 Union Avenue New Windsor, NY 12553

phone: (845) 561-2550 fax: (845) 565-0626

e-mail: nwwater@hvc.rr.com

## **SPECIFICATIONS: WATER MAINS, SERVICES & APPURTENCANCES**

- 1. WATER MAIN: Ductile-Iron, Class 350, Class 52 minimum, Cement Lining AWWA STANDARDS C104, C111, C150, C151
- 2. FITTINGS: Ductile-Iron Compact Fittings, Cement Lining, M.J. AWWA STANDARDS C104, C153
- 3. VALVES: 4" to 12" MUELLER Co. 2360 Series, resilient wedge, M.J., "NO EQUAL" AWWA STANDARD C509
  16" and up MUELLER Co. 3211 Series, Lineseal III Butterfly, M.J. "NO EQUAL"
- 4. FIRE HYDRANTS: CLOW MEDALLION, "NO EQUAL" AWWA STANDARD C502
- 5. ROADWAY VALVE BOXES: Must be manufactured in North America: General Foundry
  The Town has the right to inspect boxes before installation
  and will reject for poor casting, slag & dimensions.
- 6. SERVICE LINE MATERIAL: All brass to be manufactured by MUELLER Co.
  - a. Corporation Stop: Inlet H-15008, AWWA C-800
     Outlet Copper compression quarter bend connection, hard quarter, no swivel. "NO EQUAL"
  - b. Curb Stop: H-15209, AWWA C-800
  - c. Curb Box: H-10308 with rod, 3/4" 1", or equal
  - d. Curb Box: Roadway Box (#5 above) all over 1"
  - e. Meter Pit: 3/4" thru 2", MUELLER/McCULLOUGH "Thermal-Coil"
  - f. Tubing: Copper Type K
  - g. Couplings: H-15403, AWWA C-800
- 7. Meters: SENSUS brand, NO EQUAL, Radio (RF) Read remote, must be purchased from the Town, in cubic feet.
- 8. Tapping Sleeve: Cast iron tapping sleeves appropriate MUELLER H-619 or H-615 depending on type of pipe
  - Stainless Steel Powerseal models 3490 and 3460, Dresser Style 630 heavy stainless, Smith-Blair 665. All Flanged or MJ
  - Recommendation No size on size taps (ex. 6" tap on a 6" main) permitted without written approval by the Town Engineer or Water Superintendent.

Updated: 3/2021